

GMK325BJ106MMHT



■ Features

- Item Summary
10uF±20%, 35V,
X5R, 1210/3225 (EIA/JIS)
- Lifecycle Stage
Non-preferred
- AEC-Q200 qualified
- Standard packaging quantity (minimum)
Taping Embossed 500pcs

■ Products characteristics table

| | |
|---|---------------|
| Capacitance | 10 uF ± 20 % |
| Case Size (EIA/JIS) | 1210/3225 |
| Rated Voltage | 35 V |
| tan δ (max) | 5 % |
| Temperature Characteristic (EIA) | X5R |
| Operating Temp. Range (EIA) | -55 to +85 °C |
| High Temperature Loading (% Rated Voltage) | 150 % |
| Insulation Resistance (min) | 100 MΩ · μF |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (173 subst.) | Yes |
| Halogen Free | Yes |
| Soldering | Reflow |

■ External Dimensions

| | |
|-------------|---------------|
| Dimension L | 3.2 ±0.30 mm |
| Dimension W | 2.5 ±0.20 mm |
| Dimension T | 2.5 ±0.20 mm |
| Dimension e | 0.60 ±0.30 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.